



MULTI-CHANNEL GAS ANALYSER

Biogas 905



ADOS GmbH

Instrumentation and Control

P.O. Box 500 444 · 52088 Aachen · FRG

Trierer Strasse 23 – 25 · 52078 Aachen · FRG

Tel: +49 (0) 241 / 97 69 - 0

Fax: +49 (0) 241 / 97 69 - 16

E-Mail: info@ados.de

www.ados.de



Application

The **Biogas Analyser 905** monitors either continuously or intermittently, the gas components contained in the Biogas and optionally, monitors the surrounding air to provide an early warning of dangerous, explosive and non-combustible gases and vapours.

Accessories

Signal horn, warning light, warning banner, plotter.

Other accessories will be offered, according to the measurement tasks required.

Fields of Application

- ☒ Monitoring of Biogas components
- ☒ Warning of explosive gas mixtures
- ☒ Warning of gases that endanger health
- ☒ Warning of non-combustible gases

Features

- ☒ Up to 5 sensors for Biogas measurements
- ☒ Up to 3 sensors for room monitoring
- ☒ Time-controlled measurements in intermittent mode
- ☒ 4-line display, each line with 16 characters
- ☒ Menu-assisted operation via 6 keys
- ☒ 16 freely configurable alarms (max. 3 per measurement point or sensor)
- ☒ Adjustable alarm threshold, from 5 – 100 % of the measurement range
- ☒ A minimum of 5 floating alarm contacts for optional assignment
- ☒ Floating service and fault contact
- ☒ 5 analog outputs, 4–20 mA
- ☒ 5 digital inputs for control functions (initiating a measurement, selection of a measurement point)
- ☒ Double measurement change-over switch in the standard housing (optional); extras by request
- ☒ Serial output RS 232 or RS 485
- ☒ Manual flow-through adjustment
- ☒ Gas components-filter system and conditioning
- ☒ Condensate collector for external installation
- ☒ High degree of operational reliability
- ☒ Low power consumption

Technical Data

Details apply, per control unit

Sensors:	Electrochemical sensors Infrared sensors Semiconductor sensors
Sensor input:	2-wire sensors (TOX 592) or 3-wire sensors (GTR 196) for warning of explosive gas mixtures
Sensor supply:	24 V DC / 200 mA max.
Test ranges:	CH ₄ : 0–100 Vol % H ₂ S: 0–500/2000/5000 ppm CO ₂ : 0–50 Vol % O ₂ : 0–21 Vol % H ₂ : 0–2 Vol % other ranges by request
Accuracy:	< ±3 %, f.s.d.
Ambient temperature:	+41 °F to +113 °F
Temperature effects:	< 5 % for a ± 68 °F change
Installation:	Wall-mounting
Output signals:	Current output 4–20 mA RS 232 or RS 485 interface; a minimum of 5 floating alarm contacts for optional assignment; 1 fault relay 1 service relay
Relay rating:	230 V, 500 VA
Voltage supply: optional:	115 V, 60 Hz 230 V, 50 Hz
Power consumption:	100 VA
Dimensions (W x H x D):	23.62 x 19.68 x 15.75 inch (9 HU)
Weight:	approx. 77.16 lbs

Measurable gases

Gas	Formula
Methane	CH ₄
Hydrogen sulphide	H ₂ S
Carbon dioxide	CO ₂
Oxygen	O ₂
Hydrogen	H ₂
other gases by request	