



ADOS[®]
e s t . 1 9 0 0

Instrumentation and Control



MULTI-CHANNEL GAS WARNING UNIT

MWVS 897



ADOS GmbH

Tel: +49 (0) 2 41 / 97 69 - 0

Instrumentation and Control

Fax: +49 (0) 2 41 / 97 69 - 16

P.O. Box 500 444 · 52088 Aachen · FRG

info@ados.de

Trierer Strasse 23-25 · 52078 Aachen · FRG

www.ados.de

since 1997
DIN EN ISO 9001
ID: 0110071011



Application

The multi-channel gas warning unit MWS 897 continuously monitors the ambient air and provides an early warning of hazardous, explosive and non-combustible gases and vapours.

Fields of Application

Monitoring of:

- Heating systems
- Garages and tunnels
- Liquid gas storage rooms
- Laboratories
- Cold-storage houses
- Plastic processing plants
- Chemical industries
- Paint manufacturing plants
- Concentration measurement of O₂
- and many more

Features

- Use of various types of measurement sensor
- Ready, fault and gas warning indicators
- Menu-aided operation, via 2 keys
- Integrated buzzer, gas half-hourly average value
- Three alarm thresholds individually adjustable from 0–100 % of test range
- Three floating alarm outputs for driving additional warning and control systems
- Floating fault contact
- Serial output RS 232, for connecting a printer or a PC
- High degree of reliability
- Low current consumption
- Plastic, wall-mounting housing
- Easy installation
- Straightforward operation

Measurable gases

Gas	Formula
Acetylene	C ₂ H ₂
Alcohol	e.g. C ₂ H ₆ O
Ammonia	NH ₃
Butane	C ₄ H ₁₀
Carbon dioxide	CO ₂
Carbon monoxide	CO
Carbon tetrachloride	CCl ₄
Chloroform	CHCl ₃
Ether	C ₄ H ₁₀ O
Helium	He
Hydrogen	H ₂
Hydrogen chloride	HCl
Methane	CH ₄

Neon	Ne
Oxygen	O ₂
Petroleum spirit	
Propane	C ₃ H ₈
Toluene	C ₇ H ₈
Xylene	C ₈ H ₁₀

Accessories

Signal horn, warning light, warning banner, ventilation control, test meters, plotter.
Additional accessories are available, depending on the system ordered.

Technical Data

Sensors:	Semiconductor sensor Heat reaction sensor Thermal conductivity sensor Fuel cell Infrared cell
Sensor inputs:	6 two-wire sensors (e.g. TOX 592) or 3 three-wire sensors (e.g. GTR 196) or 2 three-wire sensor + 4 two-wire sensors
Sensor supply:	19 V _≈ / 300 mA
Ranges:	CO 0–300 ppm NO ₂ 0–30 ppm CH ₄ 0–100 % LEL CO ₂ 0–10 Vol % further ranges on request
Accuracy:	<3%, f.s.d.
Ambient temperature:	-10 °C to +40 °C
Temperature effects:	<3 % for ± 20 °C change
Setting time (t ₉₀):	< 60 s
Installation:	Wall-mounting
Protection class:	IP 54
Output signal:	Voltage output, 1–5 V RS 232 interface 3 alarm relays, 1 fault relay
Relay rating:	230 V, 450 VA other voltages on request
Voltage supply:	230 V, 50 Hz 115 V, 60 Hz (optional) 24 V= (optional)
Consumption:	14 VA
Dimensions (W x H x D):	225 x 180 x 105 mm
Weight:	approx. 1,5 kg