



MULTI-CHANNEL GAS ANALYSER

Biogas 905



ADOS GmbH

Instrumentation and Control

P.O. Box 500 444 · 52088 Aachen · FRG

Trierer Strasse 23-25 · 52078 Aachen · FRG

Tel: +49 (0)2 41 / 97 69 - 0

Fax: +49 (0)2 41 / 97 69 - 16

info@ados.de

www.ados.de



Application

The Biogas Analyser 905 monitors either continuously or intermittently, the gas components contained in the Biogas (process control) and optionally, monitors the surrounding air to provide an early warning of dangerous, explosive and non-combustible gases and vapours.

Fields of Application

- Monitoring of biogas, landfill gas or digester gas
- Warning of explosive gas mixtures
- Warning of gases that endanger health
- Warning of non-combustible gases

Features

- Up to 5 sensors for Biogas measurements
- Up to 3 sensors for room monitoring
- Time-controlled measurements in intermittent mode
- 4-line display, each line with 16 characters
- Menu-assisted operation via 6 keys
- 16 freely configurable alarms (max. 3 per measurement point or sensor)
- Adjustable alarm threshold, from 5–100 % of the measurement range
- A minimum of 5 floating alarm contacts for optional assignment
- Floating service and fault contact
- 5 analog outputs, 4–20 mA
- 5 digital inputs for control functions (initiating a measurement, selection of a measurement point)
- Double measurement change-over switch in the standard housing (optional); extras by request
- Serial output RS 232
- Manual flow-through adjustment
- Gas components-filter system and conditioning
- Condensate collector for external installation
- High degree of operational reliability
- Low power consumption
- Water sensor for the detection of condensate break-through
- Monitoring of more than one measuring point possible

Measurable gases

Gas	Formula
Methane	CH ₄
Hydrogen sulphide	H ₂ S
Carbon dioxide	CO ₂
Oxygen	O ₂
Hydrogen	H ₂

Accessories

Signal horn, warning light, warning banner, plotter.

Other accessories will be offered, according to the measurement tasks required.

Technical Data

Details apply, per control unit

Sensors:	Electrochemical sensors Infrared sensors
Sensor input:	2-wire sensors or 3-wire sensors for warning of explosive gas mixtures
Sensor supply:	24 V DC / 200 mA max.
Test ranges:	CO ₂ : 0 - 50 Vol.% CH ₄ : 0-100 Vol.% O ₂ : 0 - 21 Vol.% (optionally continuous) H ₂ : 0 - 0,2 ... 2 Vol. % H ₂ S: 0 - 50 ppm ... 0 - 5.000 ppm (only discontinuous) other ranges by request
Accuracy:	< ±3 %, f.s.d.
Ambient temperature:	+5 °C to +45 °C
Temperature effects:	< 5 % for a ±20 °C change
Installation:	Wall-mounting
Output signals:	Current output 4–20 mA RS 232 interface a minimum of 5 floating alarm contacts for optional assignment; 1 fault relay 1 service relay
Relay rating:	230 V, 500 VA
Voltage supply: optional:	230 V / 50 Hz 115 V / 60 Hz
Power consumption:	100 VA
Dimensions (W x H x D):	600 x 500 x 400 mm (9 HU)
Weight:	approx. 35 kg